

SAFETY DATA SHEET

IDENTITY: FSC-88 WB

Date of Preparation: 1/1/18

SECTION I - Material and Manufacturer Identification

Manufacturer's Name & Address

Coastal Enterprises Company
P.O. Box 4875
Orange, CA 92863-4875

Emergency Telephone Numbers:

N/A

For Information: Call (800) 845-0745

Product Name: FSC-88 WB

ID Number: NA

Chemical Name: Water Based Filler

Formula: Mixture

DOT Proper Shipping Name: N/A

DOT Hazard Classification: NA

SECTION II - Composition / Information on Ingredients

PRODUCT COMPOSITION:	APPROX. WGT.%	ACGIH TVL TWA	STEL	OSHA PEL TWA	STEL	UNITS
A. HAZARDOUS Aqua Ammonia Cas # 1336-21-6 35 b	.01% ppm		25 b	35 b		none
B. NON-HAZARDOUS: Water Cas # 7732-18-5	20-50%	NA	NA	NA	NA	NA
Calcium Carbonate Cas # 1317-65-3	10-50%	NA	NA	NA	NA	NA
Acrylic polymers Non-Hazardous	30-90%	None	None	None	None	None

SECTION III - Hazards Identification

Emergency Overview: NA

Potential Health Effects: None

Ingestion: None known

Skin Contact: Prolonged or repeated contact may cause mild skin irritation

Inhalation: May cause headache, nausea, and irritation of nose, throat, and lungs.

Eye Contact: May irritate eyes.

Medical Conditions Aggravated: None known

Subchronic (target organs) Effects: None known

Chronic Effects / Carcinogenicity: This product or one of its ingredients present .1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IRAC, or OSHA.

Products / Ingredients: This space reserved for special use

Principle Routes of Exposure: Skin / Eye Contact / Inhalation

Other: None known

SECTION IV - First Aid Measures

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and get medical attention. Never give anything by mouth to an unconscious person.

Skin: Wash with soap and warm water. Consult a physician if irritation persists.

Inhalation: Move subject to fresh air.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Note to Physician: None known

SECTION V - Fire Fighting Measures

Flash Point: Non-combustible, will burn only after water is driven off.

Method: PMCC

Ignition Temp: Not Applicable

Flammable Limits in Air Lower: None (water)

Flammable Limits in Air Upper: None (water)

Sensitivity to Mechanical Impact: (Y/N) No

Sensitivity to Static Discharge: Not expected

Extinguishing Media: All standard fire fighting media

Special Fire Fighting Procedures: Fire fighters should wear breathing apparatus

SECTION VI - Accidental Release Measures

Action to be Taken If Material is Released or Spilled: Soak up an inert material and put in a container for disposal. Wash walking surfaces with soap and warm water to reduce slipping hazard. Keep spills and cleaning runoff out of municipals, sewers, and open bodies of water.

SECTION VII - Handling and Storage

Precautions to be Taken in Handling and Storage: Avoid contact with eyes

SECTION VIII - Exposure Control / Personal Protection

Engineering Controls: None

Respiratory Protection: Use in well-ventilated area

Protective Gloves: Yes

Eye and Face Protection: Safety glasses

Other Protective Equipment: None known

Ventilation: Use in a well-ventilated area

SECTION IX - Physical and Chemical Properties

Boiling Point: 100°C / 212°F

Vapor Pressure: NA

Vapor Density: NA

Freezing Point: 0°C/32°F

Evaporation Rate (Butyl Acetate = 1): <1

Physical State: Liquid

PH: 8-9

% Volatile by Volume: 30-90%

Melting Point: NA

Specific Gravity: 1.5

Solubility in Water: 99%

Voc: (EPA Method 24): GPL 50

Odor: None (mild)

SECTION X - Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Thermal Decomposition / Combustion Products: Thermal decomposition may yield styrene and acrylic monomers.

Incompatibility (Materials to Avoid): None known

Conditions to Avoid: None known

SECTION XI - Toxicological Information

Acute Oral LD50 (MG/KG): Rat > 5000 mg/kg

Acute Dermal LD50 (MG/KG): Rabbit 5000 mg/kg
Acute Inhalation LC50 (MG/L): None found
Other: Non-irritating to skin (rbt) minimally irritating to eye (rbt).
Ames Test: Unknown

SECTION XII - Ecological Information

No data at this time

SECTION XIII - Disposal Information

Disposal Method: Disposal should be made in accordance with federal, state and local regulation.

SECTION XIV - Transportation Information

No Regulations

SECTION XV - Regulatory Information

No chemicals in this product are regulated at the amounts used.

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR)

SARA TITLE 3: Section 311/312 Categorizations (40 CFR 370): This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

SARA TITLE 3: Section 313 Information (40 CFR 372): This product does not contain a chemical which is listed in section 312 at or above the minimum concentrations.

CERLA Information (40CFR 302.5): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or state and local emergency planning committees under the Superfund Amendments and Re-authorizations Act (SARA) Title III Section 304.

Waste Classification: When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC) however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

United States: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Pennsylvania: Any material listed as Non-Hazardous in the CAS REG NO. Column of Section 2, Composition / Information on Ingredients of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-To-Know Act.

SECTION XVI - Additional Information

This product contains the following substance (S) identified by OSHA, WHMIS, or the ACGIH as hazardous. During normal use, the material will not present an exposure risk. Once the product has reached its final state and is sanded or abraded, dust may occur.

20-50% Calcium Carbonate (1317-65-3)
Exposure limit total dust 15/mg/m³ (OSHA) 10 mg/m³ (ACGIH)
Exposure limit; respirable dust 5 mg/m³ (OSHA)
LD50: No data found LC 50: No data found

The information contained herein is based on data believed by Coastal Enterprises Company to be accurate, but we do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones, which exist. Anyone intending to rely on any recommendation or to use any equipment technique or material mentioned should also satisfy himself that he could meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use and whether there is any infringement of patents, is the sole responsibility of the user.
