# SAFETY DATA SHEET

<b>IDENTITY:</b> PB Hard Coat – Part B	Date of Preparation: 1/19/2018				
SECTION I - Material and Manufacturer Identification					
Manufacturer's Name & Address	Emergency Telephone Numbers:				
Coastal Enterprises Company P.O. Box 4875 Orange, CA 92863-4875	<u>Transportation Emergencies:</u> Call CHEMTREC (800) 424-9300 (202) 483-7616 (Collect) from Alaska & Hawaii				
For Information: (800) 845-0745	<u>Health Emergencies:</u> Call LOS ANGELES POISON INFORMATION CENTER (24 hrs.) (800) 356-3129				
Product Name: PB Hard Coat – Part B					

**Chemical Names:** Two Component Water Based Foam Coating **Formula:** Component B (Liquid)

PB Hard Coat is not considered a Hazardous Material under the OSHA Hazard Communication Standard (29CFR)

SECTION II -	Hazardous	Ingredients
--------------	-----------	-------------

INGREDIENT		AC	GIH TVL	OSH	IA PEL	
<b>A. HAZARDOUS</b> Aqua Ammonia ppm	<b>% WT.</b> .4%	<b>CAS NO. TWA</b> 1336-21-6	<b>STEL</b> 25 b	<b>TWA</b> 35 b	STEL UNITS none	35 b
B. OTHER INGREDIENTS 3-iodo-2-propynyl butyl NA	.15%	55406-53-8	NA	NA	NA	NA
Carbarmate 2 (Hydroxymethyl) amino ethar NA	nol .15%	34375-28-5	NA	NA	NA	NA
C. NON-HAZARDOUS: Water NA	20-30%	773248-5	NA	NA	NA	NA
Acrylic polymers none	60-70%	Proprietary	none	none	none	none

# **SECTION III - Physical Data**

VAPOR DENSITY

BOILING POINT 100°C/212 °F SPECIFIC GRAVITY 1.03

VOC (EPA METHOD 24) GPL "0" VAPOR PRESSURE N/A FREEZING POINT 0°C/32 °F

**APPEARANCE/ODOR** Milky liquid/dry power/ Slight ammonia (mild) SOLUBILITY IN WATER 99% MELTING POINT (F)

% VOLATILE BY VOLUME EVAP. RATE (BUTYL ACETATE=1): N/A 20-40%

VOC: (EPA METHOD 24): GPL "0"

**PH:** 7-8

### SECTION IV - Fire and Explosion Hazard Data

FLASH POINT: Non combustible wet. Will burn only after water is driven off. >300°F METHOD: PMCC **FLAMMABLE LIMITS IN AIR:** Lower: None (water) Upper: None (water) **EXTINGUISHING MEDIA:** All standard firefighting media. Water, fog, foam or dry chemical. SENSITIVITY TO MECHANICAL IMPACT: No SENSITIVITY TO STATIC DISCHARGE: Not expected

SPECIAL FIREFIGHTING PROCEDURES: Firefighters must wear breathing apparatus.

### **SECTION V** - Reactivity Data

STABILITY: Stable Unstable х CONDITIONS TO AVOID: Excessive heat wet. **INCOMPATIBILITY:** Metal salts will coagulate this product. HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield CO, CO2, NOx, acrylic monomers. HAZARDOUS POLYMERIZATION: May Occur \_\_\_\_ Will Not Occur \_X\_

# SECTION VI - Health Hazard Data

**CARCINOGENICY:** This product or one of its ingredients present, 0.1% or more, is not listed as a carcinogen or suspected carcinogen by NTP, TRAC, OSHA or Prop. 65. **EMERGENCY & FIRST AID PROCEDURES:** Ingestion - May result in gastric disturbances. Eye Contact - May irritate eyes. Inhalation – May cause headache, nausea, irritation of nose, throat and lungs. Skin Contact – Prolonged or repeated contact may cause mild skin irritation.

#### PRIMARY ROUTE(S) OF ENTRY Skin \_\_\_ Eye Contact X Breathing X Swallowing X

#### **EMERGENCY AND FIRST AID PROCEDURES**

If Breathed: Move subject to fresh air. Aid in breathing, if necessary, and get immediate medical attention.

In Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

If On Skin: Wash with soap and warm water.

If Swallowed: Induce vomiting. Slowly dilute with 1-2 glasses of water or milk and get medical attention. Never give anything by mouth to an unconscious person.

## SECTION VII - Precautions For Safe Handling and Use

SPILLAGE OR RELEASE: Soak up with an inert material and put in a container for disposal. Wash walking surfaces with soap and warm water to reduce slipping hazard. This material is not regulated under RCRA or CERLA (Superfund). Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHOD: Disposal should be made in accordance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Avoid contact with eyes. PROTECT FROM FREEZING

TOXICOLOGICAL INFORMATION: Do not release into waterways or drains that lead to waterways.

VENTILATION: Use in well ventilated area. RESPIRATORY PROTECTION: Use a NIOSH/MSHA approved respirator as necessary. Observe OSHA regulations. PROTECTIVE GLOVES: Yes. EYE AND FACE PROTECTION: Safety glasses.

The information contained herein is based on data believed by Coastal Enterprises Company to be accurate, but we do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. Anyone intending to rely on any recommendation or to use any equipment, technique or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use and whether there is any infringement of patents, is the sole responsibility of the user.