SAFETY DATA SHEET

IDENTITY: PB Resin Modified Epoxy Resin – Part A **Date of Revision:** 1/19/2018

SECTION I - Material and Manufacturer Identification

Manufacturer's Name & Address	Emergency Telephone Numbers:			
Coastal Enterprises Company P.O. Box 4875 Orange, CA 92863-4875	Transportation Emergencies: Call CHEMTREC (800) 424-9300 (202) 483-7616 (Collect) from Alaska & Hawaii			
For Information: (800) 845-0745	<u>Health Emergencies:</u> Call LOS ANGELES POISON INFORMATION CENTER (24 hrs.) (800) 356-3129			
Product Name: PB Resin Modified Epoxy Resin – Part A				
DOT Proper Shipping Name: Epoxy Resin				

DOT Hazard Classification: N/A UN/NA Number: N/A

SECTION II - Composition / Information On Ingredients

4.4' - ISOPROPYLIDENEDIPHENOL EPICHLOROHYDRIN POLYMER

C.A.S. NO. 25068-38-6

100%

95

SECTION III - Physical / Chemical Characteristics

BOILING POINT: VAPOR PRESSURE: VAPOR DENSITY: EVAPORATION RATE: SOLUBILITY IN WATER: SPECIFIC GRAVITY: PERCENT VOLATILE: VOLATILE ORGANIC COMPOUNDS: VOC LESS H2O & EXEMPT SOLVENTS: PH: VISCOSITY: MELTING POINT: APPEARANCE AND ODOR: >200 ° C <1 MMGH >1 AIR=1 N/A NEGLIG. 1.16-1.18 Water = 1 NEGLIG. N/A N/A N/A >120 Poises N/A Very light, yellow liquid

SECTION IV - Fire & Explosion Hazard Data

AUTOIGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, foam.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing, including helmet, selfcontained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs; face mask, and protective covering for exposed areas of the head. UNUSUAL FIRE AND EXPLOSION HAZARDS: Under fire conditions, this material can polymerize and decompose which can cause pressure build-up in closed containers. Explosive rupture is possible.

NFPA HAZARD CODES: HEALTH: 2 **FIRE:** 1 **REACTIVITY: 0**

UNUSUAL REACTION HAZARD: N/D

OSHA FIRE HAZARD CLASS: Class IIIB combustible liquid

SECTION V - Reactivity Data

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur. HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS: Carbon monoxide and carbon dioxide, aldehydes.

INCOMPATIBILITY: Materials/conditions to avoid: Strong acids, strong bases, amines

SECTION VI - Environmental Information

SPILL RESPONSE: Observe precautions from other sections. Ventilate area. Contain spill. Cover with absorbent material. Collect spilled material. Clean up residue. Place in an approved metal container. Seal the container.

RECOMMENDED DISPOSAL: Cure product according to product instructions. Incinerate uncured waste in an industrial or commercial incinerator. Dispose of completely cured (or polymerized) material in a sanitary landfill.

ENVIRONMENTAL DATA: An epoxy resin produced by the condensation reaction of epichlorohydrin and bisphenol-A. These raw materials are consumed in the process. Residual levels of epichlorohydrin are typically 2 to 3 PPM.

Keep out of surface waters, sewers and waterways entering or leading to surface waters. Notify authorities if an exposure to the general public or environment occurs, or is likely to occur. The reportable quantity for a leak of this product is 50,000 lbs. which is based on the presence of epichlorohydrin an approximate of 2 to 3 PPM. **REGULATORY INFORMATION:** Since regulations vary, consult applicable regulations or authorities

before disposal. U.S. EPA hazardous waste number = None (not U.S. EPA hazardous).

EPCRA HAZARD CLASS: FIRE HAZARD: No PRESSURE: No **REACTIVITY: Yes** ACUTE: Yes CHRONIC: Yes

SECTION VII - Suggested First Aid

INGESTION: Drink 2 glasses of water and get medical attention. Never give anything by mouth to an unconscious person.

SKIN: Immediately wash skin with soap and large amounts of water. Remove contaminated clothing. If signs/symptoms occur, call a physician. Wash contaminated clothing before reuse and dispose of contaminated shoes.

INHALATION: Move subject to fresh air. Aid in breathing, if necessary. If breathing is difficult, get immediate medical attention.

EYES: Immediately flush eyes with large amounts of water. Get immediate medical attention.

SECTION VIII - Precautions For Safe Handling and Use

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

EYE PROTECTION: Avoid contact with eyes. Wear unvented goggles during operations in which exposure is likely.

SKIN PROTECTION: Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended. Neoprene, Nitrile Rubber.

RECOMMENDED VENTILATION: Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION: Avoid breathing of vapors. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION: Wash hands after handling and before eating.

RECOMMENDED STORAGE: Store away from acids. Store away from heat. Keep container dry.

FIRE AND EXPLOSION AVOIDANCE: Not applicable.

EXPOSURE LIMITS:

INGREDIENT	VALUE UNIT	TYPE	AUTH	1
4,4' Isopropylidenediphenol	None	None	None	None
Epichlorohydrin Polymer	None	None	None	None

Phenol, 4, 4 (1-Methylethlidene) Bis-Polymer with (Chloromethyl) Oxirane (CAS# 25068-38-6)

SKIN NOTATION: Listed substances indicated with "y" under skin refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH / OSHA

SECTION IX - Health Hazard Data

EYE CONTACT: Mild eye irritation can include redness, swelling, pain, and tearing. **REPEATED EXPOSURE MAY CAUSE:** Severe eye irritation which can include redness, swelling, pain, tearing, cloudy appearance of the cornea, impaired vision, and possible permanently impaired vision.

SKIN CONTACT: Allergic skin reaction can include redness, swelling, blistering, and itching. A moderate skin irritation can include redness, swelling, itching, and dryness.

INHALATION: Central nervous system depression can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

IRRITATION: (Upper Respiratory) Can include soreness of the nose and throat, coughing and sneezing.

IF SWALLOWED: Ingestion is not a likely route of exposure to this product.

IRRITATION OF GASTROINTESTINAL TISSUES: Can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

CENTRAL NERVOUS SYSTEM DEPRESSION: Can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

SECTION X - Regulatory Information

SARA TITLE 3 – Toxic Chemicals List: This product does not contain a toxic chemical for routine annual 'Toxic Chemical Release Reporting' under Sec. 313 (40 CFR 372)

CERLA Information (40 CFR 302.4): Not listed.

Waste Classification: Not a hazardous waste under RCRA (40 CFR 261)

Toxic Substances Control Act (TSCA):

All ingredients of this product are listed on the TSCA Inventory. This product contains the following chemical(s) that require export notification under Section 12, (b) of the Toxic Substance Control Act: Bisphenol A Diglycidyl Ether.

TSCA Export Notification:

This product contains chemical(s) which is (are) regulated by TSCA 12 (b) regulation and it is required that proper export notification shall be sent to EPA prior to shipping out of the United States of America. Bisphenol A Diglycidyl Ether (CAS # 001675-54-3)

Canadian Inventory Status:

All components included on the Domestic Substances List (DSL).

The following chemicals are specifically listed by individual states: Other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements, you should contact the appropriate agency in your state.

STATE LISTED COMPONENT

	STATE CODE	
*Epichlorohydrin (CAS #106-89-8)	2PPM	MA.CA65, PA
Phenol, 4, 4' – (1-Methylethlidene) BIS-, Polymer with (Chloromethyl) Oxirane (CAS #25068-38-6)		NJ, PA

*This product contains a chemical or chemicals known to the State of California to cause cancer and/or reproductive toxicity.

CA = California Haz. Subst.: CA65 - California Safe Drinking Water and Toxic Enforcement Act.

List: FL = Florida Subst. List: IL = Illinois Tox. Subst. List: MA = Massachusetts Subst. List: ME = Main Haz. Subst. List: MN = Minnesota Haz. Subst. List: NJ = New Jersey Haz. Subst. List: PA = Pennsylvania Haz. Subst. List: RI = Rhode Island Haz. Subst. List: DSC Canadian Inventory

Caution: Misuse of empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

The information on this data sheet represents our current data and best opinion as to the proper use and handling of this product under normal conditions. Any use of the product which is not in

conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

The information contained herein is based on data believed by Coastal Enterprises Company to be accurate, but we do not assume any liability for the accuracy of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use, and whether there is any infringement of patents, is the sole responsibility of the user.